

ATTENTION

***Before starting installation — Please read this page completely.
Professional upholstery installation is recommended.***

These seat foam sets (backrest cushion & bottom seat cushion) have been carefully inspected before boxing, be careful not to rip or tear the foam removing it from the box. If you do tear the foam, the tear can be repaired using a spray adhesive. When you begin tearing your old seats apart take note that the cotton padding will no longer be necessary. Remove the wire from your old seat cover listing area & save it your new seat covers may not have them. Compare the width & length of your new seat cover listings to your new seat foams listings grooves. Check your seat frame, springs, and burlap for weak broken or missing springs and torn or worn out burlap. If your frame, springs or burlap need repair contact your parts dealer for new bottom side support springs or a complete seat spring assembly. Failure to do so will decrease the life of your new foams.

PLEASE NOTE: No credit or exchanges will be allowed by manufacturer on torn units or after installation has been started.

Now you are ready to begin installation. Place your new seat foams on your seat spring assembly and center with your seat cover turned inside out place on the foam. Line up the listings with the groove again be sure the seat foam and upholstery are centered. Using hog ring pliers and hog rings take the listing and wire through the foam to the wire assembly. Continue until both sides are complete and seat upholstery is snug. Now you are ready to turn the seat cover skirt right side out, at this time you may need a second person. On a clean firm surface turn your seat up side down and evenly & firmly compress your seat foam and spring assembly while doing so hog ring your seat cover to the frame. If your seat bottom is a 1967-68-69 Camaro/ Firebird you will require a second person to compress your seat while you are pulling the seat cover and plastic edging about 1" past the groove in the frame. To complete installation release pressure on seat evenly.

If you have any problems, questions, or comments please feel free to call our tech line @ 1-859-408-2007.